



- 2/3"
 - 5 Mega
 - MANUAL
 - C-mount
 - METAL
- 最大Sensor尺寸 五百萬像素 手動光圈 C型接口 金屬材質

- 1.支持五百萬像素2/3"相機
- 2.有聚焦鎖緊螺釘和光圈鎖緊螺釘
- 3.低畸變成像
- 4.結構設計緊湊，光學性能優異

型號		PMS-123628M5	
分辨率		500萬像素;160lp/mm (中心) 125lp/mm (周邊)	
焦距		12-36mm	
光圈範圍		F2.8-F16	
最大Sensor尺寸		2/3" (8.8mm X 6.6mm ϕ 11mm)	
視場角 (對角×水平×垂直)	2/3"	50.8° × 41.2° × 31.2° (wide)	17.2° × 13.8° × 10.4° (tele)
	1/2"	37.7° × 30.3° × 22.8° (wide)	12.6° × 10.1° × 7.6° (tele)
成像範圍		0.15m-∞ (wide) 0.45m-∞ (tele)	
對象大小 (在最近對焦距離處)		163.4mmX130.7mmX98.0mm (wide) 152.0mmX121.6mmX107.4mm (tele)	
操作方式	聚焦	手動 (鎖定機構)	
	光圈	手動 (鎖定機構)	
畸變率	2/3"	-3.4%@y=5.5mm (wide)	1.4%@y=5.5mm (tele)
	1/2"	-2.2%@y=4.0mm (wide)	0.9%@y=4.0mm (tele)
后焦距(in air)		18.93mm (wide) 18.87mm (tele)	
接口		C型	
濾鏡尺寸		M40.5×0.5mm	
工作溫度		-10°C ~ +50°C	
重量		188.0g	